



KK-60



Brief Introduction

King Clima KK-60 model is direct engine driven 6KW cooling solutions for minibus or vans with 4-4.5m length.

Features

- ◆ Compact design
- ◆ Cooling for special zone
- ◆ Independent installation
- ◆ Independent control and system

Technical of KK-60 Minibus Air Conditioner

Model		KK-60
Cooling Capacity		6400W/5500Kcal/22000Btu
Power Consumption (24V)		<330W
Installation Type		Rooftop Mounted
Driven Type		Direct Engine Driven
Max Operating Temp. (°C)		50°C
Evaporator	Type	Hydrophilic aluminum foil with internal ridge copper tube
	Air Flow Volume (m³/h)	600m³/h
	Fan Motor	3-speed Centrifugal Type
	No. Or Fan Motor	2pc
Condenser	Type	Aluminum Foil with Internal Ridge Copper Tube
	Air Flow Volume (m³/h)	1800m³/h
	Fan Motor	Axial Type
	No. Or Fan Motor	2pc
Compressor	Brand	Sanden China Compressor
	Model	SD5H14
	Displacement	138cc/r
	Compressor Oil Type	PAG100
	Weight(KG)	5KG
Evaporator Blower		3-speed centrifugal type
Condenser Fan		Axial flow
Compressor		Valeo TM21, 215 cc/r
Refrigerant		R134a
Length/Width/Height (mm)		956*761*190
Weight (KG)		30
Application		4-4.5m Minibus or Vans

