

## Brief Introduction of K-560

K-560 Truck chiller refrigeration truck units have front mounting and rooftop mounting, driven by vehicle engine and apply for medium or big trucks with 22~30m<sup>3</sup> Truck body box or 5.2 meter length truck body to keep temperature range from -18°C to +15°C.

The Truck reefer units with chiller and freezing function for transporting fresh fruits, milk, ice cream, vegetables, meat, dairy products and seafood ...

## K-560 Truck Refrigeration System Optional Functions

- AC220V/1Ph/50Hz or AC380V/3Ph/50Hz
- Optional electric standby system AC 220V/380V

## K-560 refrigeration system Features:

- Multi-function controller with microprocessor control system of truck refrigeration units
- The units with CPR valve will better protect compressors, especially in extremely hot or cold place.
- Adopt Eco-friendly refrigerant : R404a
- The Hot gas defrosting system with Auto and manual is available for your choices
- Rooftop mounted unit and slim evaporator design
- Strong refrigeration, cooling fast with short time
- High-strength plastic enclosure, elegant appearance
- Quick installation, simple maintenance and low maintenance cost
- Famous brand compressor: such as Valeo compressor TM16, TM21, QP16, QP21 compressor, Sanden compressor, highly compressor etc.
- International Certification : ISO9001, EU/CE etc

Model		K-560
Temperature Range(In Container)		- 18℃ ~ +15℃
Cooling Capacity	0℃	4600W
	-18℃	2400W
Compressor	Model	TM16/QP16
	Displacement	162cc/r
	Weight	8.9kg
Condenser	Fan	2/2600m <sup>3</sup> /h
	Dimensions	1148X475x388mm
	Weight	31.7kg
Evaporator	Fan	3/ 1950m <sup>3</sup> /h
	Dimensions	1080×600×235 mm
	Weight	25kg
Voltage		DC12V / DC24V
Refrigerant		R404a/ 1.6- 1.7kg
Defrosting		Hot gas defrosting(Auto./ Manual)
Application		22~30m <sup>3</sup>
Option Function		heating, data logger, standby motor

## Application

